



MODEL SCL-24 CABINET LOCK	A	B	C	MODEL SCL-24 KEEPER	A	B	C
	2.625	1.125	1.063		1.063	1	0.688
NOTE: FASTENERS NOT SHOWN - ALL DIMENSIONS IN INCHES							

SOLENOID CABINET LOCK - MODEL SCL-24

Features

- Fail secure
- Fits into most size limited applications
- Holds an amazing 600 lbs.
- Intermittent duty
- 24 VDC 200 mA current draw
- Indoor use only

Operating Temperature

0 to 43C [32 to 110F]

How to order

Part #
SCL-24

Description
Solenoid Cabinet Lock 24VDC



SOLENOID CABINET LOCK - MODEL SCL-24 (cont'd)

Architectural Specifications

- A. The SCL-24 Solenoid Cabinet Lock shall be produced by an ISO 9001 certified manufacturer
- B. The Solenoid Cabinet Lock shall have a limited lifetime warranty covering malfunction and abuse.
- C. The LOCK shall only be available in a 24VDC model.
- D. The LOCK shall be fail secure and fit into most size limited applications.
- E. The LOCK shall hold 600 pounds and shall provide a strong level of security for cabinet locking applications.
- F. The LOCK shall not support outdoor use or use where the cabinet will be released for extended periods of time.