




PRODUCT FEATURES

- Fully-encrypted AES 128 wireless communication
- Online transaction audit trail capability
- Low battery signaling and reporting
- Suitable for outdoor use
- Up to 40,000 cycles per battery
- Green status LED indicator
- Two models are available to support low frequency or high frequency cards
- › Low frequency model supports PROX and EM PROX
- › High frequency model supports iCLASS, iCLASS Seos™, iCLASS SE, ISO14443B UID, Mifare, Mifare Plus, Desfire SE, Desfire EV1, NFC
- Protected by SecuriCare 3-Year, No Fault Warranty

PRODUCT SPECIFICATIONS

- Dimensions:**
4.25" x 1.8" x 1.0"
[108mm x 46mm x 26mm]
- Operating Temperature:**
-40 to +122F [-40 to +50C]
- Compliant:**
FCC, CE and IC Compliant
- Shipping Weight:**
2.83oz [80g]
- Battery:**
1 x 3V CR2 Lithium Battery



R100-1H

Wireless Reader and Apero® Hub

Surface Mounted—No Drilling

The R100-1H surface mounted wireless reader and pre-prepared Apero hub offers an elegant way to extend access control to glass, stone, granite or marble entryways. Installation is easy, requires no drilling or pulling of wires and can adhere in minutes. A complement to an electronic locking solution, glass entryways can now integrate robust access control while maintaining a clean, wireless appearance.

MODELS

MODEL	PART #	Description
R100-1H-SE		R100, iCLASS SE, Wholesale Kit with 1:1 Hub
R100-1H-PA		R100, PROX, Wholesale Kit with 1:1 Hub
R100-DCA		R100 Dress Cover, Aluminum

